



Radiator Blowout: Wheel Loaders

Standard Operating Procedure

REFUSE
DISPOSAL
DIVISION

Greens Processing

Periodic radiator blowout is essential! By keeping the cooling system free from dust, debris and trash, the operator ensures positive cooling. Benefits include long engine life, improved engine performance, reduced fuel consumption and exhaust emissions.

1. Always allow five-minute cool down prior to engine shut-off.
2. Ensure you are wearing all safety gear (i.e., glasses, gloves, respirator, dust masks, etc.).
3. Secure Park mode – all attachments lowered.
4. Open up protective radiator grill guards, bonnet or cowling.
5. Split transmission cooler, if applicable.
6. Blowout transmission cooler, radiator and air cooler.
7. Close machinery guards and bonnets.
8. Ensure all latches and locks are in place and air indicators are in the green.

***NOTE – This blowout procedure is to be done a minimum of four (4) times a day. More frequently, if necessary.**

Benefit of Compliance to Instruction:

- Increased life span of machinery
- Increased productivity
- Reduced fuel consumption

Consequence of Non-Compliance to Instruction:

- Machinery breakdown -> high cost of replacement parts
- Reduced productivity
- Increased emissions
- Disciplinary action

Environmental Management System (EMS) –ISO 14001

PROCESS MAP #: GP-1.0

Reviewed by: Gary Gobel, Landfill Superintendent

Approved by: Steven F. Fontana, Deputy Environmental Services Director, Refuse Disposal

The on-line version and secured hardcopy are the controlled documents. The secured hardcopy will be identified by a “Controlled Copy” stamp (in red) and RDD Deputy Director signature. Any other documents are uncontrolled. Verify revision level status on-line or contact the EMR